



Low Voltage Combination Wave Lightning Surge Simulator **CWS 120G**

- IEC/EN 61000-4-5
- GB/T 17626.5

Features

- > 5.7-inch color touch screen front panel operation
- > Test voltage 1 V ~ 1200 V
- > Source impedance 2 Ω
- > Built-in surge voltage measurement module
- > Real-time display for peak voltage and peak current
- > Test sequence function
- > Ethernet and RJ45 interfaces, used for PC remote control and printing test reports

Introduction

The CWS 120G is specially designed for simulating low voltage surge pulse disturbances phenomenon, which can be used in surge protection device (TVS tube, TSPDs, SIDAC, surge suppressor and wafer or package level) immunity test. Its output voltage can be adjustable from 1 V to 1200 V, which totally meet the test requirement of IEC/EN 61000-4-5 and GB/T 17626.5.

The product adopts 3-rd generation control platform and features high system integration, intelligent control and easy operation.

Application Areas



Technical Parameters

In Compliance with	IEC 61000-4-5
Test Voltage	1 V ~ 1200 V, $\pm 10\%$
Voltage Waveform	Rise Time: $1.2 \mu\text{s} \pm 30\%$ Time to half value: $50 \mu\text{s} \pm 20\%$
Test Current	0.5 A ~ 600 A $\pm 10\%$
Current Waveform	Rise Time: $8 \mu\text{s} \pm 20\%$ Time to half value: $20 \mu\text{s} \pm 20\%$
Source Impedance	2 Ω
Polarity	+, -, +/-
Repetition Time	1 s ~ 9,999 s
Counter	1 ~ 9,999
Trigger Mode	Manual, Auto, External Trigger

General Parameters

Display Screen	5.7" TFT touch screen
Working Power	AC 110 V/220 V, $\pm 10\%$, 50/60 Hz
Fuse	6 A
Maximum Power Consumption	200 W
Communication Mode	Ethernet Lan (RJ45 interface)
Working Status Indication	LED indication and LCD display in front panel
Failure Detection	LCD display in front panel and stop work when failure occurs
Dimension	19 inches/4U rack, 450 mm * 192 mm * 620 mm
Weight	Approx. 20 kg
Atmospheric Pressure	86 kPa ~ 106 kPa
Ambient Temperature	15°C ~ 35°C
Relative Humidity	45% ~ 75%

Standard Accessories

Power Cord, User Manual, Test Cables, Flat grounding cable, Fuse

Optional Accessories

1	Wide-band Current Probe	Model: CM 0103M 5 kA, 0.1 V / A	
2	PC Control Software	Model: Corelab Support Windows 7/8/10 /11; support Ethernet Interface; support sequence test, easy to operate, generate & export test report.	

SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.