



Coupling/Decoupling Network for Shielded Lines

CDN 405S1

- IEC 61000-4-5
- EN 61000-4-5
- GB/T 17626.5

Features

- > Max. pulse voltage 6 kV; Max. working current 5 A
- > Support 10 Mbit/s signal transmission rate
- > Support EMC generators of all brands, quick connection without extra adaptation
- > Coupling Waveforms are 1.2/50 μ s, 8/20 μ s
- > Suitable for shielded Ethernet with standard BNC interface

Introduction

The CDN 405S1 Coupling/Decoupling Network for Screened Lines is designed in compliance with IEC/EN 61000-4-5, GB/T 17626.5, and fully complies with the performance and cabling specifications for CDNs.

The CDN 405S1 is a coupling/decoupling network designed for surge immunity testing of single-core screened cables. Its max. test voltage is 6 kV and max. current reaches 5 A. The CDN 405S1 supports test requirements for cables with single-end grounded shielding and double-end grounded shielding.

Application Areas



Technical
Parameters

Coupling Waveform	1.2/50 μ s, 8/20 μ s
Pulse Voltage	6 kV
Coupling Method	Direct connection
Data Rate	10 Mbit/s
Working Current	Max. 5 A
EUT Connection Port	BNC

General
Parameters

Weight	Approx. 10 kg
Dimension	360 mm(L) * 220 mm(W) * 135 mm(H)
Enclosure Material	Aluminum alloy
Ambient Temperature	15°C ~ 35°C
Relative Humidity	45% ~ 75%
Package	Carton


Standard Accessories

Short-circuit Plug, Test Cables, Grounding Wire


Optional Accesories

1	Lightning Surge Simulator	Model: CWS 600 Output Voltage: 0.25 kV ~ 6.0 kV	
---	---------------------------	--	---


Connection Schematic



Standard Schematic 1 (Shielded Cable with Both Ends Grounded)



Standard Schematic 1 (Shielded Cable with Single End Grounded)



SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.