



Impulse Voltage Simulator

VSG 384A

- IEC 60384-14
- UL 60384-14

Features

- > 5.7 color touch screen
- > Max. test voltage up to 15 kV
- > Support test scheduling function with easy operation
- > Support automatic multi-range switching function

Introduction

The VSG 384A impulse voltage simulator is developed in accordance with IEC 60384-14 and UL 60384-14 standards. It can generate a 1.7/46 μ s pulse voltage waveform with a maximum output voltage of 15 kV.

The VSG 384A complies with impulse withstand voltage test requirements for fixed capacitors. It is equipped with 4 built-in test ranges and features automatic range switching.

Application Areas



Technical Parameters

Test Voltage	1 kV ~ 15 kV, ±10%	
Voltage Waveform (Cx=10 nF±2% Rs=45 Ω)	Front time: 1.7 μs (0/+50)%	
	Time to Half Value: 46 μs (0/+50)%	
Energy Storage Capacitor (CT)	0.25 μF	
Range	Cx≤0.0039 μF	Rs=62 Ω ±10%
	0.0039 μF < Cx≤0.012 μF	Rs=45 Ω ±10%
	0.012 μF < Cx≤0.018 μF	Rs=27 Ω ±10%
	0.018 μF < Cx≤0.027 μF	
Polarity	Positive, negative, alternative	
Repetition Time	5 s ~ 99 s (the shortest time depends on the test voltage)	
Counter	1 ~ 999	
Trigger Mode	Automatic, manual, external trigger	
Note: Since CT, RP, RS and CP are fixed, the circuit efficiency will decrease and the output voltage will decay significantly when the capacitance of the EUT (Cx) is much larger than 10 nF.		
Tr and Td are defined in accordance with IEC 60060-1.		

General Parameters

Display Screen	5.7-inch TFT touch screen
Working Power	AC 220 V, $\pm 10\%$, 50 Hz/60 Hz
Power Consumption	Max. 500 W
Fuse	6 A
Communication Mode	Ethernet LAN
Working Status Indication	LED indication and LCD display on the front panel
External Trigger Input	BNC, 5 V TTL
CRO Trigger Input	BNC, 5 V TTL
Run Control Input	BNC, 5 V TTL
Grounding Method	Flat grounding wire
Dimension	6U rack, 450 (W)*280 (H)*620 (D) mm
Weight	Approx. 40 kg
Ambient Temperature	15°C ~ 35°C
Relative Humidity	45% ~ 75% RH (no condensation)
Atmospheric Pressure	86 kPa ~ 106 kPa

Standard Accessories

Power Cord, Test Cable, Grounding Wire, Fuse, Calibration Capacitor ($C_x=15\text{kV } 10\text{nF}$), User Manual

SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.