



Coupling Transformer

TPT-7637-4C1000B

- ISO 7637-4
- ISO 21498-2
- MES PW 67602

Features

- > High load current;
- > Large power capacity;
- > Wide frequency range;
- > 22U rack, easy for transportation

Introduction

The TPT-7637-4C1000B wideband coupling transformer is designed for immunity tests required by standards such as ISO 21498-2 and ISO 7637-4. It can transmit time-harmonic (sinusoidal) signals and pulse signals to the EUT through magnetic coupling, featuring distortion-free waveform, high power capacity and physical isolation from the EUT.

Application Areas



Technical Parameters

Frequency Range	300 Hz ~ 150 kHz
Max. Coupling Voltage	80 V _{pp} (Open Circuit, 2:1)
Max. Coupling Current	400 A _{pp} (Short Circuit, 4:1)
Turns Ratio	2:1 and 4:1
Max. EUT Current/ Voltage*	600 A DC/ 1,000 V DC @Max 20 min; 1,000 A DC/ 1,000 V DC @Max 10 min
Dimension	800 mm (W)*1,150 mm (H)*1,405 mm (D)
Weight	570 kg
Ambient Temperature	15°C ~ 35°C
Relative Humidity	45% ~ 75%
Atmospheric Pressure	86 kPa ~ 106 kPa
* The Max. continuous operating duration of the coupling transformer is limited by the Max. EUT current. It is recommended that the operating time shall not exceed 20 minutes at 600 A DC / 1,000 V DC, and shall not exceed 10 minutes at 1,000 A DC / 1,000 V DC.	

Standard Accessories

Power Cord, Test Cable, Grounding Wire, User Manual

SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.