



Calibration Device of Peak Impulse Current

PIC 1134

■ IEC 61000-4-11

■ IEC 61000-4-29

Features

> Max. withstand inrush current: 500 A

Introduction

The PIC 1134 Peak Impulse Current Calibration Device is specially designed to calibrate the peak inrush current driving capability during voltage dips.

It complies with IEC 61000-4-11 and IEC 61000-4-29.

Application Areas



Technical Parameters

Peak Inrush Current Driving Capability	Max. 500 A (for 220 V ~ 240 V power supply) Max. 250 A (for 100 V ~ 120 V power supply)
Capacitance	1,700 μ F
Discharge Resistance	4,700 Ω
Current Monitoring Output	100 A:1 V
Max. Rated Voltage	AC 230 V, DC 350 V
Dimensions	225 mm (L)* 135 mm (H)* 369 mm (D)
Weight	Approx. 6 kg

Standard Accessories

Test Cable*2, Coaxial Cable*1

Test Connection Diagram



SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.