



Calibrated Resistor Box

R/1-16Ω/1134

IEC 61000-4-11

■ IEC 61000-4-34

Features

> High-precision non-inductive resistor

Introduction

R/1-16 Ω/1134 calibration resistor box meets the requirements of IEC 61000-4-11 and IEC 61000-4-34, with resistance adjustable from 1 Ω to 16 Ω and Max. power of 4,000 VA.

Application Areas



Technical Parameters

Model	R/1-16/1134
Resistance	1 ~ 16 Ω
Power	4,000 W

Manual Resistance Adjustment Series Connection Schematic

Ω	1 (4000W)	2 (4000W)	4 (4000W)	5 (4000W)	6 (4000W)
1	1				
2		2			
3	1	2			
4			4		
5	1		4		
6		2	4		
7	1	2	4		
8	1	2		5	
9	1	2			6
10			4		6
11				5	6
12		2	4		6
13	1	2	4		6
14	1	2		5	6
15			4	5	6
16	1		4	5	6

SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.