



Ripple Signal Generator

RSG 40C20

- ISO/TS 7637-4
- ISO 21498
- ISO 11452.8
- VW 80300
- GJB 151B

Features

- > Equipped with overvoltage and overcurrent protection functions
- > Multiple operation modes
- > Low-frequency power amplifier 10 Hz ~ 300 kHz, Max. output voltage 80 V_{PP}, Max. output current 40 A_{PP}
- > Output voltage accuracy ± 0.2 V
- > Supports closed-loop AC voltage and current testing
- > Ethernet and RJ45 interfaces, used for PC remote control and printing test reports

Introduction

The RSG 40C20 Ripple Signal Generator complies with ISO/TS 7637-4, ISO 21498, VW 80300, GJB 151B and ISO 11452.8, fulfilling the requirements of Pulse B for transient conducted measurement of new-energy vehicle electric drive systems and high-voltage components.

Adopting our 3rd-generation control platform, the instrument delivers intelligent control and easy operation. Parameters can be configured via the AutoLab software for one-click test execution, with support for closed-loop AC voltage and current testing.

Application Areas



Technical
Parameters

Frequency Range	10 Hz ~ 300 kHz
Frequency Step	0.01 Hz
Max. Output Voltage	80 V _{PP}
Max. Output Current	40 A _{PP}
Ripple Dwell Time	2 s ~ 999 s, resolution 0.1 s
Output Voltage Accuracy	± 0.2 V

General
Parameters

Working Power	AC 220 V, ±10%, 50 Hz ~ 60 Hz
Max. Power Consumption	800 W
Dimension	4U rack, 450(H) mm * 190(D) mm * 620(W) mm
Weight	Approx. 25 kg
Atmospheric Pressure	86 kPa ~ 106 kPa
Ambient Temperature	15°C ~ 35°C
Relative Humidity	45% ~ 75%, RH (no condensation)

Standard Accessories


Power Cord, User Manual, Test Cable, Fuse

Optional Accessories

1	Coupling Transformer	Model: TPT-7637-4C100B Max. unsaturated voltage: 160 V _{PP} Max. coupling current: 100 A _{PP} Max. EUT current: DC 100 A Max. EUT voltage: DC 1,000 V Turns ratio: 1:1 Frequency: 10 Hz ~ 300 kHz	
2	PC Control Software	Model: AutoLab Support Windows 7/8/10/11; Users can easily customize test sequences and arbitrary waveforms. The system automatically identifies and enables flexible test report generation.	

Connection Diagram


Line - to - line:



4

Connection Diagram

HV+ line-to-ground:



SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.