



Unbalanced High Frequency Line Impedance Stabilization networks **VHF-LISN NBM3-16**

- CISPR16-1-4-
- CISPR16-2-3

Features

- > 4mm Banana plug input/output, safe and stable
- > Power adapter for quick conversion from 4 mm banana terminals to standard power plugs (EU, US, CN, etc.)

Introduction

The VHF-LISN NBM3-16 is a unbalanced VHF-LISN designed in accordance with CISPR 16-1-4, which specifies the design and performance requirements for high-frequency line impedance stabilization networks.

It is suitable for single-phase 3-wire power lines with a maximum current of 16 A.

Application Areas



Technical Parameters

Frequency	30 MHz ~ 300 MHz
Max. AC Voltage (Line-to-ground)	250 V
Max. DC Voltage (Line-to-ground)	400 V
Max. Current	16 A
Type of EUT Port	4 mm Banana terminal (L/N/PE)
Type of AE Port	4 mm Banana terminal (L/N/PE)
Input Impedance (at EUT port)	L: $160\ \Omega \pm 40\%$ @30 MHz to 300 MHz N: $60\ \Omega \pm 40\%$ @30 MHz to 300 MHz PE: $90\ \Omega \pm 40\%$ @ 30 MHz to 300 MHz
Phase (at EUT port, PE-RG)	$0 \pm 40^\circ$ @30 MHz to 300 MHz
Isolation (AE-EUT)	>40 dB @30 MHz to 300 MHz


General Parameters

Enclosure Material	Aluminum material
Dimension	25 (L)*16 (W)*10 (H) mm
Weight	Approx. 4 kg
Ambient Temperature	5 °C ~ 40 °C
Relative Humidity	20% ~ 80%
Atmospheric Pressure	86 kPa ~ 106 kPa

Standard Accessories

Test Cable, Fuse, User Manual

Standard Schematic Diagram



SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.