

Airborne AC/DC Power Characteristic Test System **PPS 45C10**



- MIL-STD-704
- RTCA/DO-160
- HB 20326
- GJB 181

Features

- > Support harmonics output
- > Support ripple closed-loop test
- > Full-power four-quadrant power supply
- > Adaptive remote compensation function
- > Wide frequency range: DC ~ 200 kHz
- > Max. test current 105 A ((higher current ratings are available on request)
- > Max. output power 20 kW (higher power ratings are available on request)
- > Voltage and current monitoring and protection
- > Ethernet RJ45 interfaces for PC remote control and printing test reports
- > Built-in arbitrary waveform generator for any complex waveforms editing

Introduction

The PPS 45C10 Airborne AC/DC Power Characteristic Test System features wide voltage and current dynamic range, in compliance with MIL-STD-704F, DO160 S16/S18, HB 20326.8, GJB 181-86 and GJB 181A/B. Its output voltage distortion is below 0.3% under all load conditions, with frequency coverage from DC to 200 kHz. It supports tests for DC systems as well as AC system.

Adopted real-time processor technology, the system is equipped with high-performance PC and Corelab test software. It enables arbitrary waveform editing to simulate complex waveforms and provides preset waveforms and EMC and aerospace standard test items. The software also supports automatic test report generation.

Application Areas



Technical Parameters

AC Test System	
Max. AC Voltage	L-N/0 V ~ 450 V L-L/0 V ~ 779 V @0.001 Hz ~ 200.00 Hz L-N/0 V ~ 400 V L-L/0 V ~ 692 V @0.001 Hz ~ 400.00 Hz L-N/0 V ~ 300 V L-L/0 V ~ 519 V @0.001 Hz ~ 1000.00 Hz
Max. AC Current	Single phase: 105 A Three phases: 35 A
Output Power	20 kW
AC Voltage Accuracy	$\pm (0.01\% + 0.05\% \text{ F.S. } ^{*1})$
AC Current Accuracy	$\pm (0.01\% + 0.05\% \text{ F.S. } ^{*1})$
DC 270 V Test System	
Max. DC Voltage	636 V
Max. DC Current	105 A
Output Power	20 kW
DC Voltage Accuracy	$\pm (0.01\% + 0.05\% \text{ F.S. } ^{*2})$
DC Current Accuracy	$\pm (0.1\% + 0.2\% \text{ F.S. } ^{*2})$
DC 14 V & DC 28 V Test System	
Max. DC Voltage	80 V
Max. DC Current	30 A
Output Power	2.4 kW
DC Voltage Accuracy	$\pm (0.2\% + 0.2\% \text{ F.S. } ^{*3})$
DC Current Accuracy	$\pm (0.2\% + 0.5\% \text{ F.S. } ^{*3})$
Notes: *1: F.S. (full scale) refers to max. voltage 450 V and current 105 A for AC test system. *2: F.S. (full scale) refers to max. voltage 636 V and current 105 A for DC 270 V test system. *3: F.S. (full scale) refers to max. voltage 80 V and current 30 A for DC 14 V & DC 28 V test system.	

Voltage/Current Setting Resolution	0.01 V/ 0.01 A
Voltage/Current Display Resolution	0.01 V/ 0.01 A
Harmonics Voltage	0 V ~ 20 V
Harmonics Voltage Setting Resolution	0.001 V
Harmonics Voltage Display Resolution	0.001 V
Harmonics Frequency	1 kHz ~ 50 kHz (higher frequencies are available on request)
Harmonics Frequency Setting Resolution	0.001 Hz
Harmonics Frequency Display Resolution	0.001 Hz
Total Voltage Harmonic Distortion (THDv)	$<0.3\%$
Ripple Noise @20 MHz bandwidth	$V_{PP} \leq 2.4 \text{ V}$ $V_{rms} \leq 0.4 \text{ V}$

General Parameters

Display Screen	15.6" embedded touch screen
Protection	Overcurrent, overvoltage, undervoltage, overpower, overtemperature protection
Power Input Interface Type	63A-6H, industrial circular connector
Control Port Communication Interface	Ethernet LAN (RJ45 interface)
Working Power Supply	Three phases AC 380 V, 50 Hz/60 Hz
Grounding Connection	Dual independent grounding, flat grounding cable
Front/ Rear Panel Wiring Terminal	32 A banana terminal & 100 A solid terminal
Dimension	600 (W)*1,225 (H)*900 (D) mm
Weight	Approx. 192 kg
Ambient Temperature	15 °C ~ 35 °C
Relative Humidity	45% ~ 75%
Atmospheric Pressure	86 kPa ~ 106 kPa

Standard Accessories

Power Cord, User Manual, Test Cables, Grounding Cable, Network Cable
--

SUZHOU 3CTEST ELECTRONIC CO., LTD.

Address: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

E-mail: globalsales@3ctest.cn

Service: service@3ctest.cn

Tel: +86 - 512 - 68077192

Web: www.3ctest.com



3CTEST is always striving for product innovation and quality improvement. Product appearance and technical specifications are subject to change without further notice.